

DECLARATION OF PERFORMANCE

DOP FQ-015

1. Unique identification code of the product-type:

DOP FQ-015

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

The Wall

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

For use as floor covering in buildings (see EN 14041) according to the manufacturer's specifications.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Falquon GmbH, Am Hünengrab 18, D-16928 Pritzwalk

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if relevant):

Institut für Holztechnologie Dresden gemeinnützige GmbH,
Zellescher Weg 24, D-01217 Dresden

not applicable

Notified Body

certificate of constancy of performance

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not applicable

9. Declared performance

| Essential characteristics | Performance | Harmonised technical specification |
|-----------------------------------|---------------------|------------------------------------|
| Reaction to fire | B _{fl} -s1 | EN 14041: 2004/AC:2006 |
| Content of Pentachlorophenol | < 5 ppm | EN 14041: 2004/AC:2006 |
| Formaldehyd Emissions | E1 | EN 14041: 2004/AC:2006 |
| Slip resistance | DS | EN 14041: 2004/AC:2006 |
| Electrical behavior (dissipative) | NPD | EN 14041: 2004/AC:2006 |
| Electrical behavior (conductive) | NPD | EN 14041: 2004/AC:2006 |
| Electrical behavior (antistatic) | NPD | EN 14041: 2004/AC:2006 |
| Thermal conductivity [W/mK] | 0,571 | EN 14041: 2004/AC:2006 |
| Water-tightness | NPD | EN 14041: 2004/AC:2006 |

NPD: No performance determined

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed for and on behalf of the manufacturer by:

Dr. Thomas Grafenauer / Geschäftsführer

(name and function)

Pritzwalk, 01.11.2023

(place and date of issue)



(signature)